

la marzocco



gb5 s



GB5 S

**elegant design married
with proven reliability**

AVAILABLE CONFIGURATIONS

////

no. groups: **2 | 3 | 4**

configurations: **EE | AV | ABR**

Equipped with proprietary La Marzocco electronics and advanced temperature stability, the GB5 S combines classical European design with cutting edge performance. The red lilies on the sides recall our Florentine heritage, while partially exposed groups offer a streamlined barista working experience. The machine provides control over boiler temperature, brewing volume, automatic cleaning cycles, and more to keep high quality coffee flowing even during the busiest hours.

GB5 S HIGHLIGHT



classic italian design

The gracious lines and harmonious curves of the GB5 S speak to the La Marzocco heritage of design and intention. The understated side shields, elegant Florentine lilies, and subtle insignia of il marzocco on the cup rail combine to give this



machine the feel of an heirloom built to stand the test of time.

FEATURES



piero group caps (AV and ABR)

Re-engineered internal water path that increases temperature stability

dimnable barista lights (AV and ABR)

3-stage LED lights for eco, on, and brewing modes allow you to focus on your extraction and the cup

la marzocco app compatible

auto backflush

easy-rebuild steam valve

Engineered so the valve can be serviced from the front of the machine without needing to be removed

pro touch steam wands (optional)

Vacuum-insulated double-walled steam wands remain cool while delivering high-volume dry steam

clog reducing flow restrictors

A flow restrictor integrated into the solenoid valve reduces scale formation and clogging while ensuring a consistent flow rate.

SPECIFICATIONS	2 group	3 group	4 group
dimensions (W x D x H)	30.3" x 25.2" x 18.5"	38.2" x 25.2" x 18.5"	47.6" x 25.2" x 18.5"
weight (lbs)	149.9	172	231.5
voltage (VAC, phase, Hz)	208-240, 1, 60	208-240, 1, 60	208-240, 1, 60
element wattage	5200	6800	8300
steam boiler capacity (liters)	7	11	15
brew boiler capacity (liters)	3.4	5	3.4 x2
amp service required	30	50	50
certifications	UL-197, NSF-4, CAN / CSA-C22.2 No. 109		

SALES INQUIRIES 206-706-9104 (Option 2) info.usa@lamarzocco.com www.lamarzoccousa.com